



## HEXAFLOOR

---

### Application

**This universal floor covering is used for surfaces that need to bear heavy loads.**

These stylish tiles are the ideal solution for facilitating access to your event. They can be used to create paths and car parks. Sites for trade fairs and exhibitions, access roads or work platforms can all be made accessible without any specific surface preparation. This flooring system makes it possible to give access to forklifts, cars, trucks and cranes.

### Protection of the natural surface

The tiles are also suitable for stabilizing uneven surfaces.

### Properties

Hexagonal in form, the tiles can be used to lay corners with 30°, 60° and 90° angles, making this system ideal for asymmetrical sites.

### Laying the tiles

The tiles are laid by hand.

We supply geotextiles as an underlay to protect fragile surfaces as well as our tiles from dirt.

We handle pickup and delivery, and can also see to the installation, dismantling and final cleaning upon request.

### Deliveries

Our hexagonal panels are delivered in trays.

We supply geotextiles as an underlay for particularly fragile surfaces and as protection against dirt. We require a 2.5T forklift on site to load and unload our trucks.

### Environmentally friendly, durable and economical

Hexafloor is made of 100% recycled plastic and can be recycled again once discarded after having been used for a very long time.

It has been common practice up to now to use wood or wood by-products for the above-mentioned purposes. Hexafloor helps us conserve our natural resources.

# HEXAFLOOR: TECHNICAL SHEETS

---

## SPECIAL MODEL

---

- These tiles form a seamless surface
- Tile weight: 3.1 kg
- Surface area of tile: 0.27 m<sup>2</sup>
- Colour: grey
- Material: recycled plastic, 100% recyclable, biologically and ecologically sound
- Environmental influences:
  - Heat resistant up to 60° C
  - Cold resistant
  - UV stable
  - Non-inflammable B2
- Maximum load per tile:
  - On stable surface: 5 T per tile
  - On wet or uneven surface: 3 T per tile
- Easy to lay by hand
- Transport: max. 1025 m<sup>2</sup> per trailer



## ALL-ROUND MODEL

---

- This model has handles and is therefore suitable for heavy duty purposes, but not for creating a seamless surface
- Tile weight: 3.2 kg
- Surface area of tile: 0.27 m<sup>2</sup>
- Colour: grey
- Material: recycled plastic, 100% recyclable, biologically and ecologically sound
- Environmental influences:
  - Heat resistant up to 60° C
  - Cold resistant
  - UV stable
  - Fireproof B2
- Maximum load per tile:
  - On stable surface: 6 T per tile
  - On wet or uneven surface 3.5 T per tile
- Easy to lay by hand
- Transport: max. 1165 m<sup>2</sup> per trailer